



- **Products name:** flexible flat cable
- **Model:** 20624,20798,20706,20941,2643
- **Pitch:**0.5mm、0.8mm、1.0mm、1.25mm、1.27mm、1.5mm、2.0mm、2.54mm
- **Insulation:** PET or PVC
- **Voltage & Temp. & Current Rating**
300V,105°C,0.5A
- **Numb. of conductor:** 2-60Pin
- **Lenth:** Tailored, ≥ 10 mm
- **Application:** DVD & Blue-Ray Players, Set-Top Units, Computers, Notebooks, & Tablets, Computers, Notebooks, & Tablets, Printers, 3-D Printers & Scanners,Keyboards
- **Feature:** Highly Flexible/Light Weight/Extremely Thin

- **Products name:** flexible flat cable
- **Model:** 20624,20798,20706,20941,2643
- **Pitch:**0.5mm、0.8mm、1.0mm、1.25mm、1.27mm、1.5mm、2.0mm、2.54mm
- **Insulation:** PET or PVC
- **Voltage & Temp. & Current Rating**
300V,105°C,0.5A
- **Numb. of conductor:** 2-60Pin
- **Lenth:** Tailored, ≥ 10 mm
- **Application:** GPS Systems, Built-In LCD Displays, Switch Rotary Connectors, Clock spring Mechanisms, Head liners



- **Products name:** flexible flat cable
- **Model:** 20624,20798,20706,20941,2643
- **Pitch:**0.5mm、0.8mm、1.0mm、1.25mm、1.27mm、1.5mm、2.0mm、2.54mm
- **Insulation:** PET or PVC
- **Voltage & Temp. & Current Rating**
300V,105°C,0.5A
- **Numb. of conductor:** 2-60Pin
- **Lenth:** Tailored, $\geq 10\text{mm}$
- **Application:** Membrane Switch Assemblies, Automation Systems, Instrumentation & Measurement Equipment, Industrial Equipment



- **Products name:** LVDS +FFC
- **Model:** 14P,20P,30P,40P,41P,51P
- **Pitch:**0.5mm 、1.0mm、1.25mm
- **Insulation:** PET or PVC
- **Contact plating:** Gold or Tin Over Nickel
- **Numb. of conductor:** 14-51Pin
- **Lenth:** Tailored, $\geq 10\text{mm}$
- **Application:** LED and LCD display